



ZOLI PLOSZ

FIRE EXTINGUISHING

Hand-held Fire Extinguishers.....	98
Wheeled Fire Extinguishers.....	98
Backpack Extinguishers	99
Accessories for Fire Extinguishers	99
Fire Blankets.....	99



PURPLE K DRY CHEMICAL FIRE EXTINGUISHER

- Rugged construction, easy to maintain and service
- Bar coded labels for documenting extinguisher locations, inspections, maintenance and recharging
- Temperature range: -65°F to 120°F
- Tested and certified to cUL standards

PART #	CAPACITY	DESCRIPTION
AMX B410TX	2-1/2 lb.	10B:C rated, with vehicle bracket
AMX B479T	5 lb.	30B:C rated, with vehicle bracket
AMX B460X	10 lb.	80B:C rated, tall
AMX 415X	20 lb.	120B:C rated
AMX 693X	30 lb.	160B:C rated, with brass valve



HIGH PERFORMANCE DRY CHEMICAL EXTINGUISHER

- Superior range with high (240 psi) operating pressure
- Choice of chemicals: ABC multi-purpose, BC Regular or Purple K
- Select fast flow for high flow rate, fast discharge and quicker knockdown
- Select compliance flow for long range and highest cUL ratings
- Bar coded and bilingual labels
- Temperature range: -65°F to 120°F
- cUL standards compliance

PART #	CAPACITY	FLOW	DESCRIPTION
AMX 594	13 lb.	Fast	ABC, 2A:40B:C rated
AMX 581	20 lb.	Fast	ABC, 4A:40B:C rated
AMX 567	30 lb.	Fast	ABC, 4A:40B:C rated
AMX 582	20 lb.	Fast	BC Regular, 40B:C rated
AMX 568	30 lb.	Fast	BC Regular, 40B:C rated
AMX 595	13 lb.	Fast	Purple K, 40B:C rated
AMX 580	20 lb.	Fast	Purple K, 40B:C rated, 15 seconds discharge
AMX 584	20 lb.	Fast	Purple K, 20B:C rated, 10 seconds discharge
AMX 569	30 lb.	Fast	Purple K, 40B:C rated
AMX 592	13 lb.	Compliance	ABC, 4A:80B:C rated
AMX 564X	20 lb.	Compliance	ABC, 20A:120B:C rated
AMX 589	30 lb.	Compliance	ABC, 20A:160B:C rated
AMX 566X	20 lb.	Compliance	Purple K, 120B:C rated
AMX 591X	30 lb.	Compliance	Purple K, 160B:C rated



CARBON DIOXIDE FIRE EXTINGUISHER

- Carbon dioxide is a clean, non-contaminating, odourless gas, safe for use on clothing, equipment, valuable documents or food
- Effective for Class B flammable liquid fires and is electrically non-conductive
- Manufactured and tested to cUL standards
- Comes with wall bracket

PART #	CAPACITY	DESCRIPTION
AMX 322X	5 lb.	5B:C rated
AMX 330X	10 lb.	10B:C rated
AMX 331X	15 lb.	10B:C rated
AMX 332X	20 lb.	10B:C rated



ARASAFETY

FIT5 (FIRE INTERRUPTION TECHNOLOGY)

- Kit includes FIT5, protective case and training video
- A portable powder aerosol knockdown tool
- Interrupts the fire triangle
- Safe for equipment and people
- Effective on class a, b and c fires
- Makes firefighting safer
- Deployed against real fires in the field

FNT FITSORANGE



DRY CHEMICAL NITROGEN WHEELED FIRE EXTINGUISHER

- Regular, direct pressure, nitrogen cylinder extinguishers with quick opening valve to pressurize and completely discharge the agent cylinder
- Available in 125 lb. / 150 lb. units with 16" semi-pneumatic rubber tires or 300 lb. / 350 lb. units with 36" x 6" steel wheels
- Available in ABC, BC Regular or Purple K dry chemical
- Meets Transport Canada requirements and cUL standards compliance
- Available options:
 - 75' hose
 - Stationary design
 - Pressure indicator

PART #	CAPACITY	DESCRIPTION	WHEELS
AMX 467X	125 lb.	ABC, 30A:240B:C rated	16" rubber tires
AMX 468X	150 lb.	BC Regular, 240B:C rated	16" rubber tires
AMX 469X	125 lb.	Purple K, 320B:C rated	16" rubber tires
AMX 491X	300 lb.	ABC, 40A:320B:C rated	36" steel wheels
AMX 492X	350 lb.	BC Regular, 320B:C rated	36" steel wheels
AMX 493X	300 lb.	Purple K, 320B:C rated	36" steel wheels



DRY CHEMICAL WHEELED FIRE EXTINGUISHER

- Commercial stored pressure extinguisher with cage type protection for the agent cylinder with balanced platform for transportation and operation
- Narrow width and easy rolling, semi-pneumatic, 16" rubber tires
- Chemical and pressure sealed for instant actuation
- Available with optional stationary design and tow loop

PART #	CAPACITY	DESCRIPTION
AMX 488X	125 lb.	ABC, 40A:240B:C rated
AMX 489X	150 lb.	BC Regular, 240B:C rated
AMX 490X	125 lb.	Purple K, 320B:C rated



BACKPACK FIRE PUMP



- Durable, corrosion resistant, 3/16" thick polyethylene tank with stainless steel and brass fittings
- Recessed opening with removable nylon screen and adjustable 2" shoulder straps
- Holds 5 U.S gal. and weighs 9-1/2 lbs.

OTB 20



PLASTIC INSPECTION TAG

- For outside use, unaffected by moisture, oils or grease
- 2-1/2" x 4-1/8"

RST PTAG One year
RST 4PTAG Four years



METAL INSPECTION TAG

- Four year metal inspection tag
- For monthly inspection of fire equipment and outdoor use

RST TAG 2-1/4" x 3"



STANDARD SINGLE POINT FIRE EXTINGUISHER PIN

RST SPP



BULL'S EYE TAMPER SEALS

- Sold in bags of 500
- 9" long

RST TSRED Red
RST PT7YELLOW Yellow



TAG BAGS

- For covering tags exposed to outdoor elements
- Reliable, strong and won't crack
- Heavy-duty tag bag withstands temperatures of -40°F to +130°F

RST STCP
RST HSTC Heavy-duty vinyl



FIRE EXTINGUISHER VINYL COVER

- Fluorescent red with black imprint and black trim
- Stencilled "FIRE EXTINGUISHER KEEP CLEAR"
- Made of reinforced vinyl with velcro closures

PART #	CAPACITY	WINDOW
RST EFEC10	10 lb.	Yes
RST EFEC10NW	10 lb.	No
RST EFEC20	20 lb. / 30 lb.	Yes
RST EFEC20NW	20 lb. / 30 lb.	No



HEAVY-DUTY VEHICLE BRACKET

RST VB5 10 lb.
RST VB7 20 lb.



30 LB. VEHICLE BRACKET

- 30 lb vehicle bracket for use with carbon dioxide fire extinguishers, high performance dry chemical fire extinguishers and Class D dry powder extinguishers
- Can be used with model 859 dolly cart
- Quality manufactured steel with a primed and powder coat paint finish and meets the latest U/L salt spray requirements

AMX 811



FIRE BLANKET AND CABINET

- Blanket made of two layers of woven glass fibre and one layer of fire retardant film
- Independently tested: BS6575: 1985

RST FB64 72" x 48"

